



RP327 80mm Thermal Receipt Printer

Instructions

Print	Printing method	Direct thermal printing
	Effective printing width	72mm or 64mm
	Resolution	203dpi(8 dots/mm)
	Printing speed	250mm/s
	Printing density	504 dots/line or 576 dots/line
	Character set	GB18030 (Simplified Chinese)
	Print font	ASCII Font A : 12×24 ASCII Font B : 9×24 Chinese: 24×24

	Character per line	Font A-42 lines or 48 lines/Font B-56 lines or 64 lines/Chinese-21 lines or 24 lines
Paper specification	Paper width	79.5±0.5mm
	Paper roll diameter	Φ80mm
	Paper loading	Easy paper loading
Barcodes	Barcode type	UPC-A,UPC-C,EAN-13,EAN-8,CODE39,ITF,CODEBAR,CODE93,CODE128
Reliability	MCBF	6 million lines
	Thermal printing head	100 million impulses (100km)
	Auto cutter	1 million cuts
Interface		USB ,Serial ,Ethernet
Paper out detection function		optional
Emulation		ESC/POS/OPOS
Driver		WIN98/WIN2000/WINNT/WINXP/OPOS/ WIN7/WIN8
Power supply		DC 24V,2.5A
Cash drawer Control		DC 24V, 1A
Certificate		FCC、 CE

Dimension (LxWxH)		195×145×147mm
Environment	temperature	working temperature: 0~45°C Storage : -10~50°C
	humidity	working temperature: 10-80% Storage : 10-90% (paper excluded)