



TREE MARKING PAINT

PRODUCT DESCRIPTION

An Acrylic emulsion paint based paint. Formulated to provide good performance at an economical price.

PRODUCT FEATURES

- . Ease of application
- . Good hiding power.
- . Ease of over coating.
- . Available in white
- . Ideal for marking of trees and under ground blasting identification.

TECHNICAL INFORMATION

Colour:	White
Appearance:	Matt finish
Generic type:	Acrylic Emulsion
S.G.:	1.26
Viscosity:	112 Ku
Spreading rate:	±6m ² /litre
Solvent:	Water
Artificial weathering:	Good
Opacity:	Good

SURFACE PREPARATION

Always ensure the substrate is clean, dry and free of contaminants e.g. oil, grease, wax, dirt, etc. prior to application of tree marking paint.

APPLICATION

Stir contents thoroughly, use as supplied. Do not dilute. 2 Coats of 50µ each are recommended for optimum results.

Airless spray:	Not suitable
Conventional spray:	Not suitable
Brush and Roller:	Suitable as supplied. Do not dilute.
Clean up:	Wash with Water

ENVIRONMENT

It is recommended that application be confined to the following:

Surface temperature:	Min. 15°C	Max. 40°C
Ambient temperature:	Min. 15°C	Max. 40°C
Relative humidity:	Min.0%	Max.85%
Or at least 3°C above Dew point		

DRYING TIME

Substrate Temp	Touch Dry	Hard Dry
15°C	4 hours	8 hours
20°C	2 hours	4 hours
25°C	1 hour	2 hours
30°C	30 minutes	1 hour

OVERCOATING TIMES

15°C:	8 hours
20°C:	4 hours
25°C:	2 hours
30°C:	1 hour

LIMITATIONS

Sustained cold conditions can result in paint failure.
Avoid painting on wet substrates and in wet conditions

STORAGE AND HANDLING

Store in a cool dry area, away from heat, direct sunlight and severe cold.
Shelf life: 18 months in original sealed containers.

LIMITATIONS

Sustained cold conditions can result in paint failure.
Avoid painting on wet substrates and in wet conditions.

SAFETY PRECAUTIONS

No known problems resulting from contact with skin, however, remove as soon as possible with soap and water. Avoid ingestion and contact with eyes. If ingested, seek medical attention. Do not induce vomiting. If paint contact is made with eyes, rinse eyes well with water and seek medical attention.
Do not smoke when painting.
Ensure good ventilation during painting and drying.

KEEPOUTOFREACHOFCHILDREN.

May 2020

Information Provided is based on Laboratory evaluations and data believed to be reliable.
Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for their own use.
It is not to be considered a guarantee of the products properties.

For more information contact our Factories:
Western Cape: Tel/Fax: (021) 853-8105 Mpumalanga: Tel: (013) 246-2570 Fax: (013) 246-2573